



GROUNDWATER PRESSURE RELIEF VALVE - SIDEWALL MOUNT



DESCRIPTION	MATERIAL
Body	316SS
Cover Lid	316SS
O-Ring Seal	Nitrile
PVC Adaptor	PVC-U
Hinge Assys	316SS
Screen	316SS
Hydrotite Seal	Special

DIMS mm	NB 100	NB 150
PVC-ID	114.3	168.3
PVC-OD	136	184
PVC-OAL	128	183
PRV-OAL	210	250
PRV-OPEN	0—100%	0—100%



Australian Design - Manufacture

Your highly engineered Groundwater PRV is designed for minimal maintenance and for a 100% leak proof result.
Make a call to a Q water sales engineer for the **BEST** Hydrostatic solution available today!

FEATURES:

- Sidewall mounted unit suitable for any tank where groundwater pressure may be a problem
- NB100 & NB150 dia sizes available
- Strong & durable 316SS material—corrosion resistant
- O-ring sealing with special retain feature
- Sealing surfaces machined to high tolerance
- PVC socket end for pvc pipe extension into gravel drain
- 316SS over centre hinge assembly
- 316SS debris screen to prevent entry of foreign bodies
- All welds picked and passivated for maximum longevity

Q water Pty Ltd

ABN 68 009 465 347

Head Office Ph: +61 (0) 7 3865 5555
Head Office Fax: +61 (0) 7 3865 5555

Mobile Ph **QLD**: +61 (0) 417 590 660
Mobile Ph **ALL**: +61 (0) 417 590 660

Email: sales@qwater.com.au

Web: www.qwater.com.au