


CORROSIVE & SALT WATERS **RAIN WATER CANNONS** **TURBINE GEARED**

by



Q water Pty Ltd

ABN 68 009 465 347

Head Office Ph: +61 (0) 7 3865 5555
Head Office Fax: +61 (0) 7 3865 5555



Mobile Ph **QLD**: +61 (0) 417 590 660
Mobile Ph **ALL**: +61 (0) 417 590 660

Email: sales@qwater.com.au

Web: www.qwater.com.au


Nodolini—Italy





‘NODOLINI—25deg’ CORROSIVE WATERS—WATER CANNON—TURBINE GEARED

QW-WCNS70CW-25-65-BSP



S70CW - 2 1/2" (65mm)

- Long Distance Trajectory
- 25 deg—Up Spray Angle
- 2 1/2" BSP Connection
- Minimum 4deg-360deg—Part/Full Circle
- Nozzles supplied: 28mm
- Corrosion Resistant Materials
- 4.0-9.0bar Operating Pressure Range

Nozzle Size (mm)	Pressure (kPa)	Discharge (l/min)	Radius of Throw (m)
28	405 - 506 - 607	992 - 1109 - 1215	49 - 54 - 59
30	506 - 607 - 709	1272 - 1393 - 1505	55 - 61 - 63
32	506 - 607 - 709	1449 - 1587 - 1714	57 - 63 - 66
34	607 - 709 - 810	1792 - 1935 - 2069	64 - 67 - 69
36	607 - 709 - 810	2009 - 2170 - 2320	65 - 69 - 71
38	709 - 810 - 911	2418 - 2585 - 2742	71 - 73 - 75

NODOLINI
Q water *always* has your
spraying needs covered.
Call us for a great price!

FEATURES:

1. Turbine constant geared drive irrigation sprinkler
2. Conical water discharge barrel for high/long performance
3. Adjustable jet-breaker for enhanced spray uniformity
4. No vibration – smooth operation
5. No mechanical brake required
6. Perfect functioning on steep terrain
7. Mechanical internal parts protected against corrosive waters & salt waters
8. All aluminum parts treated with anodic oxidation, plastic coatings, cataphoresis
9. All nuts, bolts, pins etc—stainless steel material (304/316SS)
10. Suitable for corrosive & salt water spraying applications

NOTE—All technical data is characteristic & not binding

Q water Pty Ltd
ABN 68 009 465 347



Head Office Ph: +61 (0) 7 3865 5555
Head Office Fax: +61 (0) 7 3865 5555

Mobile Ph QLD: +61 (0) 417 590 660
Mobile Ph ALL: +61 (0) 417 590 660

Email: sales@qwater.com.au
Web: www.qwater.com.au


Nodolini—Italy





‘NODOLINI—28deg’ CORROSIVE WATERS—WATER CANNON—TURBINE GEARED

QW-WCNS80SRCW-28-100-FLG



**OPTIONAL. THIS
MDL ONLY....
JET BREAKER KIT
ON REQUEST**



S80SRCW - 3" (80mm)

- Long Distance Trajectory
- 28 deg—Up Spray Angle
- 4"- (100mm) EN1092 Flange Connection
- Minimum 4deg-360deg—Part/Full Circle
- Nozzles supplied: 32mm
- Corrosion Resistant Materials
- 6.0-11.0bar Operating Pressure Range

NODOLINI
Q water *always* has your
spraying needs covered.
Call us for a great price!

Nozzle Size (mm)	Pressure (kPa)	Discharge (l/min)	Radius of Throw (m)
32	606 - 658 - 709	1587 - 1652 - 1714	61 - 65 - 68
34	606 - 658 - 709	1792 - 1885 - 1935	63 - 66 - 70
36	709 - 810 - 911	2169 - 2319 - 2460	71 - 74 - 80
38	709 - 810 - 911	2418 - 2585 - 2742	73 - 78 - 83
40	810 - 911 - 1013	2864 - 3038 - 3203	81 - 86 - 90
42	810 - 911 - 1013	3120 - 3310 - 3490	83 - 89 - 93
44	911 - 1013 - 1114	3630 - 3830 - 4050	92 - 95 - 99

FEATURES:

1. Turbine constant geared drive irrigation sprinkler *NOTE—All technical data is characteristic & not binding*
2. Conical water discharge barrel for high/long performance
3. **OPTIONAL**— Adjustable jet-breaker kit available (not standard supply)
4. No vibration – smooth operation
5. No mechanical brake required
6. Perfect functioning on steep terrain
7. Mechanical internal parts protected against corrosive waters & salt waters
8. All aluminum parts treated with anodic oxidation, plastic coatings, cataphoresis
9. All nuts, bolts, pins etc—stainless steel material (304/316SS)
10. Suitable for corrosive & salt water spraying applications

Q water Pty Ltd
ABN 68 009 465 347

Head Office Ph: +61 (0) 7 3865 5555
Head Office Fax: +61 (0) 7 3865 5555

Mobile Ph **QLD**: +61 (0) 417 590 660
Mobile Ph **ALL**: +61 (0) 417 590 660

Email: sales@qwater.com.au
Web: www.qwater.com.au

