



‘NODOLINI—25deg—HP10(bar)’ IRRIGATION WATER CANNON—TURBINE GEARED

QW-WCNS45HP-25-50-BSP



S45HP - 2" (50mm)

- Medium Distance Trajectory
- 25 deg—Up Spray Angle
- 2" BSP (female) Thread Connection
- Minimum 4deg-360deg—Part/Full Circle
- Nozzles Supplied: 18mm, 20mm, 22mm, 24mm
- Corrosion Resistant Materials
- 3-10bar Designed Operating Pressure Range

Nozzle Size (mm)	Pressure (kPa)	Discharge (l/min)	Radius of Throw (m)
18	303 - 405 - 506	370 - 427 - 477	34 - 37 - 42
20	303 - 405 - 506	456 - 527 - 590	36 - 41 - 46
22	405 - 506 - 607	638 - 713 - 780	42 - 47 - 49
24	405 - 506 - 607	730 - 817 - 895	43 - 48 - 52

NOTE—All technical data is characteristic & not binding

This Model - All Metal Gears

Question.....
What industrial HD sprinkler is designed for **MAXIMUM** performance—with long range capabilities?
“NODOLINI”
....of course.
Q water always has your spraying needs covered.
Call us for a great price!

FEATURES:

1. Turbine constant geared drive irrigation sprinkler
2. Conical water discharge barrel for high/long performance
3. Adjustable jet-breaker for enhanced spray uniformity
4. No vibration – smooth operation
5. No mechanical brake required
6. Perfect functioning on steep terrain
7. Suitable for the irrigation of delicate crops

Q water Pty Ltd

ABN 68 009 465 347

Head Office Ph: +61 (0) 7 3865 5555
Head Office Fax: +61 (0) 7 3865 5555

Mobile Ph **QLD**: +61 (0) 417 590 660
Mobile Ph **ALL**: +61 (0) 417 590 660

Email: sales@qwater.com.au
Web: www.qwater.com.au

