



‘NODOLINI—25deg’ IRRIGATION WATER CANNON—TURBINE GEARED

QW-WCNS60-25-50-BSP



S60 - 2" (50mm)

- Long Distance Trajectory
- 25 deg—Up Spray Angle
- 2" BSP (female) Thread Connection
- Minimum 4deg-360deg—Part/Full Circle
- Nozzles supplied: 20mm, 22mm, 24mm
- Corrosion Resistant Materials
- 4.0-6.0bar Operating Pressure Range

Nozzle Size (mm)	Pressure (kPa)	Discharge (l/min)	Radius of Throw (m)
20	405 - 455 - 506	506 - 537 - 566	41 - 43 - 45
22	405 - 455 - 506	612 - 649 - 684	43 - 45 - 47
24	405 - 455 - 506	729 - 774 - 816	45 - 47 - 49
26	455 - 506 - 557	980 - 957 - 1004	47 - 49 - 51
28	455 - 506 - 557	1053 - 1110 - 1164	50 - 52 - 54
30	506 - 557 - 607	1273 - 1335 - 1394	53 - 55 - 57

Question.....
 What industrial HD sprinkler is designed for **MAXIMUM** performance—with long range capabilities?
“NODOLINI”
of course.
 Q water always has your spraying needs covered. Call us for a great price!

NOTE—All technical data is characteristic & not binding

FEATURES:

1. Turbine constant geared drive irrigation sprinkler
2. Conical water discharge barrel for high/long performance
3. Adjustable jet-breaker for enhanced spray uniformity
4. No vibration – smooth operation
5. No mechanical brake required
6. Perfect functioning on steep terrain
7. Suitable for the irrigation of delicate crops

Q water Pty Ltd
ABN 68 009 465 347

Head Office Ph: +61 (0) 7 3865 5555
Head Office Fax: +61 (0) 7 3865 5555

Mobile Ph **QLD**: +61 (0) 417 590 660
Mobile Ph **ALL**: +61 (0) 417 590 660

Email: sales@qwater.com.au
Web: www.qwater.com.au

