


## ‘NODOLINI—25deg’ IRRIGATION WATER CANNON—TURBINE GEARED

QW-WCNS70SR-25-65-FLG



### S70 Super - 2 1/2" (65mm)

- Long Distance Trajectory
- 25 deg—Up Spray Angle
- 2 1/2" EN Flange Connection
- Minimum 4deg-360deg—Part/Full Circle
- Nozzles supplied: 28mm, 30mm, 32mm, 34mm, 36mm, 38mm, 40mm
- Corrosion Resistant Materials
- 4.0-9.0bar Operating Pressure Range

**Question.....**  
What industrial HD sprinkler is designed for **MAXIMUM** performance—with long range capabilities?

**“NODOLINI”**  
....of course.

*Q water always has your spraying needs covered. Call us for a great price!*

Nozzle Size (mm)	Pressure (kPa)	Discharge (l/min)	Radius of Throw (m)
28	405 - 506 - 607	992 - 1109 - 1215	49 - 54 - 59
30	506 - 607 - 709	1272 - 1393 - 1505	55 - 61 - 63
32	506 - 607 - 709	1449 - 1587 - 1714	57 - 63 - 66
34	607 - 709 - 810	1792 - 1935 - 2069	64 - 67 - 69
36	607 - 709 - 810	2009 - 2170 - 2320	65 - 69 - 71
38	709 - 810 - 911	2418 - 2585 - 2742	71 - 73 - 75
40	709 - 810 - 911	2788 - 2810 - 2910	74 - 77 - 80

**\*NOTE—All technical data is characteristic & not binding\***

#### FEATURES:

1. Turbine constant geared drive irrigation sprinkler
2. Conical water discharge barrel for high/long performance
3. Adjustable jet-breaker for enhanced spray uniformity
4. No vibration – smooth operation
5. No mechanical brake required
6. Perfect functioning on steep terrain
7. Suitable for the irrigation of delicate crops

**Q water Pty Ltd**  
ABN 68 009 465 347

Head Office Ph: +61 (0) 7 3865 5555  
Head Office Fax: +61 (0) 7 3865 5555

Mobile Ph **QLD**: +61 (0) 417 590 660  
Mobile Ph **ALL**: +61 (0) 417 590 660

Email: [sales@qwater.com.au](mailto:sales@qwater.com.au)  
Web: [www.qwater.com.au](http://www.qwater.com.au)

