



‘NODOLINI—28deg’ IRRIGATION WATER CANNON—TURBINE GEARED

QW-WCNS80SR-28-80-100FLG



S80 Super - 3" (80mm)

- Long Distance Trajectory
- 28 deg—Up Spray Angle
- 4" - (100mm) EN1092 Flange Connection
- Minimum 4deg-360deg—Part/Full Circle
- Nozzles supplied:
32mm, 34mm, 36mm, 38mm
- Corrosion Resistant Materials
- 6.0-11.0bar Operating Pressure Range

Question.....
What industrial HD sprinkler is designed for **MAXIMUM** performance—with long range capabilities?

“NODOLINI”
....of course.

Q water always has your spraying needs covered. Call us for a great price!

Nozzle Size (mm)	Pressure (kPa)	Discharge (l/min)	Radius of Throw (m)
32	606 - 658 - 709	1587 - 1652 - 1714	61 - 65 - 68
34	606 - 658 - 709	1792 - 1865 - 1935	63 - 66 - 70
36	709 - 810 - 911	2169 - 2319 - 2460	71 - 74 - 80
38	709 - 810 - 911	2418 - 2585 - 2742	73 - 78 - 83
40	810 - 911 - 1013	2864 - 3038 - 3203	81 - 86 - 90
42	810 - 911 - 1013	3120 - 3310 - 3490	83 - 89 - 93
44	911 - 1013 - 1114	3630 - 3830 - 4050	92 - 95 - 99

NOTE—All technical data is characteristic & not binding

FEATURES:

1. Turbine constant geared drive irrigation sprinkler
2. Conical water discharge barrel for high/long performance
3. Adjustable jet-breaker for enhanced spray uniformity
4. No vibration – smooth operation
5. No mechanical brake required
6. Perfect functioning on steep terrain
7. Suitable for the irrigation of delicate crops

Q water Pty Ltd

ABN 68 009 465 347

Head Office Ph: +61 (0) 7 3865 5555
Head Office Fax: +61 (0) 7 3865 5555

Mobile Ph **QLD**: +61 (0) 417 590 660
Mobile Ph **ALL**: +61 (0) 417 590 660

Email: sales@qwater.com.au

Web: www.qwater.com.au

